



Po Box 41

Alva, Fl 33920

Dragster Rules

(This is designed to be a run what you bring class)

1. Any air-cooled lawnmower engine single or twin cylinder
2. A scatter shield is **required** unless the mower has an aluminum flywheel
3. ANY Gear Ratio
4. Must use lawnmower frame, may use front or rear engine
5. Front and rear tire size open (see **tire tread rule for tread**)
6. Wheelie bars are mandatory.
8. Wheel base not to exceed 72". (Center to center of axles)
9. Must have brakes capable of locking rear wheels.
10. Throttle must return to idle if let go.
11. All wheels must be pinned or bolted.

General Rules

- ▶ **No Mower will be allowed to exceed 44" in overall width**
- ▶ **Fuel tanks and batteries must be adequately protected from collisions.**
- ▶ **No protrusions outside of tires on the sides.**
- ▶ **BREAKAWAY SAFETY SWITCHES (WITH TETHER) MUST BE USED IN ALL CLASSES**
- ▶ **Gasoline fuel only**
- ▶ **Tires: (Rear) Turf style type tire. Final decisions on tread will be up to Technical inspector and Technical assistant. Front Tires must be "Turf" type tires.**
- ▶ **No modifications to stock flywheel period. (Cutting drilling etc.) Must have functioning charging system. Technical inspectors will randomly check charging system for proper voltage (this will let us know that the fly wheel has not been modified)**
- ▶ **Racer numbers must be high contrast, 4" tall and placed on all four sides so the announcer can see them!!**
 - a. Racer ***must*** put his number on the right side of his/her mower when not using machine he/she registered
 - b. Only one person may use a number. In other words one man one number.
 - c. If a racer is not racing his own mower, he/she must start at the back of the field.

NOTICE!!

We only race for fun, plastic trophies, and to ENTERTAIN the Spectators, do not lose sight of that concept.

[continued on back]

DRAG RULES MAY BE CHANGED THROUGHOUT THE YEAR AS WE MAY NEED TO ADD MORE CLASSES.

Scatter shields

(Minimum requirement)

Scatter shield will be made from minimum 1/8" thick steel, the height and contour of blower housing, and use 1" strap around starter cut out. (as shown) May bolt to blower housing or extend brackets down to bolt to frame DRAGSTERS WILL NEED 2 BARS ACROSS TOP OF FLYWHEEL, MADE OF 1" FLAT STOCK BY 3/16" AS SHOWN IN PICTURE BELOW.



DRAGS

DOUBLE elimination & must have 6 paid racers to run for trophies

▶ Drags will be approximately 85 yards long. (=255')

▶ Race pairing will be set by drawing pills.

▶ Drags will be at the beginning or at the end of the event.

Drags Scoring

1st Place – 30 pts

2nd place 20 pts

all others 10pts

Notice to Racers

▶ **The flag man shall be in total control of the racing surface and will make the final determination in any racing decision.**

▶ Drivers must wear approved helmet, long pants, gloves, racing collars and ankle high shoes. You must also have adequate eye protection, goggles or helmet face shield and brakes. Without these you cannot race.

NOTICE!!

We only race for fun, plastic trophies, and to ENTERTAIN the Spectators, do not lose sight of that concept.